

SMB 3.0 Protocol Package

Industry's premiere validation system for SMB storage

Overview

The SMB 3.0 dialect extends SMB2 and is part of Microsoft Windows 8 and Windows Server 2012. The benefits of SMB 3.0 include lower CPU overhead in the compute tier with improved client caching, fault tolerance and reliability with features such as transparent failover, and high availability with scale-out and multichannel functionality.

While SMB 3.0 promises reliability and performance at par with SAN technologies, robust validation of the protocol must take place before it can be deployed in production environments. The Load Dynamix SMB 3.0 protocol package allows storage, development and QA engineers to build complex workloads that represent real product environments, emulating clients or servers acting as clients at high scale.

Equipment manufacturers can improve the robustness and performance of their SMB 3.0 server implementations. IT organizations and service providers can perform capacity assessments of the storage tiers and ensure clients and servers are configured and tuned properly to take advantage of the SMB 3.0 protocol benefits.

Highlights

- Industry's most advanced SMB validation system
- Control and schedule metadata operations together with data read / writes for the highest degree of realism
- Create highly nested SMB files and shared paths structures
- Stress the SMB infrastructure using asynchronous operations with SMB threading
- Gain full support of all major SAN, NAS and Object protocols




Figure 1: The Load Dynamix SMB 3.0 client emulation.

Key Features

Client Emulation Realism	<ul style="list-style-type: none">• Realistic emulation of SMB 3.0 clients with the ability to combine NAS/SAN protocols and versions from a single interface• Supported CIFS/SMB dialects include 2.002, 2.1, and 3.0• Configurable network options supporting VLAN tagging, IPv4, IPv6 and MAC address assignment with increment schemes for emulation of millions of unique clients• Key authentication mechanisms including NTLMv1/v2 and Kerberos• SMB 3.0 Signing.
Multichannel & Performance	<ul style="list-style-type: none">• Ability to emulate multichannel scenarios to contrast performance gains when using different number of channels and mixed network interfaces speeds• Use credit, compound request, thread block and async block constructs for validation of SMB multiplexing and asynchronous behavior
Fallover	<ul style="list-style-type: none">• Make use of application instance IDs to validate if SMB 3.0 file servers can maintain context when applications failover to different client nodes• Configure persistent/durable handles to test transparent client recovery of SMB 3.0 under negative conditions such as network or server failures
Offload / Client Caching	<ul style="list-style-type: none">• Server-side copy and copy offload commands to assess performance gains and traffic reduction improvements of these operations• Configure emulated clients to use file/directory leasing with various oplocks to understand client caching synchronization behavior, assess increases in file server scalability and reduction in network bandwidth consumption
File System Creation / Data Verification	<ul style="list-style-type: none">• Create complex file system structures with varying file sizes and directory levels• Support for reading and writing large files• Data verification options to ensure the integrity of data written to target storage<ul style="list-style-type: none">- Innovative Data Compressibility and Deduplicability algorithm
Automation	<ul style="list-style-type: none">• Automate any task needed with the protocol commands supported using scripting languages: Perl, Ruby and Python

Key Features Continued

Commands	<p>Low-level command sequencing control within scenarios to emulate any complex workload that represents hypervisor, OS, application and device behaviors. Commands supported across CIFS/SMB dialects include:</p> <ul style="list-style-type: none">• Session Requests: Negotiate, Session Setup, Logoff, Tree Connect/Disconnect, Echo• File Requests: Create, Close, Flush, Read, Write, Lock, Query/Set Info• Directory Requests: Create, Change Notify, Query Directory• IOCTL/FSCTL Requests: Get DFS Referral, Server Side Copy, Resume Key Request, Resiliency Request, Query Network Interface, Validate Negotiate Info, Offload Read/Write• Create Contexts: Durable Connect V1 & V2, Lease Request V1 & V2, Application Instance ID, Query on Disk ID, Request Maximal Access Info• MS-RPC: NetShareGetInfo, NetShareEnum, NetWkstaGetInfo, NetWkstaUserEnum
----------	---

Statistics

Actions	<ul style="list-style-type: none">• Action counts or Actions/sec (average for all or individual Actions)
Commands	<ul style="list-style-type: none">• Command counts (attempts, successes, failures or aborts)
Details	<ul style="list-style-type: none">• Command transmission/receipt OK/Fail/Drop in packets/sec or kilobits/sec
Response Time	<ul style="list-style-type: none">• Command response time (average for all or individual commands)
Throughput	<ul style="list-style-type: none">• Packet or byte throughput on per command or total basis
Data Verification	<ul style="list-style-type: none">• Data verification operations attempts, successes, failures
Latency Time (server results only)	<ul style="list-style-type: none">• Server response latency average in seconds, micros or milliseconds

Supported Platforms

- Load DynamiX 1G Series Appliances
- Load DynamiX 10G Series Appliances
- Load DynamiX Unified Series Appliances
- Load DynamiX Enterprise Series Appliances
- Load DynamiX Virtual Series Appliances



Sales
sales@virtualinstruments.com
1.888.522.2557

Training
training@virtualinstruments.com

Website
virtualinstruments.com